



Granito Impregnator – Technical Data

Description:

EcoStone Solutions Granito Impregnator is a premium impregnating, natural look, water based treatment for granite to provide maximum stain protection. Allows vapor transmission. Also used as a grout sealer.

Directions

Always test in an inconspicuous area before general use.

1. Make sure surface is clean, vacuuming or sweeping off all debris.
2. Mask off and protect areas such as baseboards or adjacent surfaces not intended for treatment.
3. Make sure surface is clean and dry prior to application.
4. EcoStone Solutions Granito Impregnator may be applied to damp surfaces one hour after moisture has been removed.
5. Apply an even coat using a paint pad, paint brush, paint roller, or low-pressure sprayer delivering a coarse wet spray.
6. Allow penetration for 10-15 minutes, then wipe off all remaining product immediately.
7. A full cure can be expected in 48-72 hours. Foot traffic can begin after 4 hours.
8. Reapply Granito Impregnator as needed for periodic maintenance. This will depend on traffic patterns, sun exposure, maintenance procedures, etc.

For use on:

Granite	Limestone
Slate	Sandstone
Clay Products	Grout

Suitable also for:

Travertine	Marble
------------	--------

Coverage:

300-1500 SF (30-139 Sq meters) per coat per gallon depending on the porosity and texture of the material, method of application, humidity, and surface temperature.

Available in:

Quarts, Gallons, 5 gallon pails, 55 gallon drums

- No chlorinated solvents
- No petroleum distillates
- VOC compliant in all states
- Environmentally responsible
- Easy to use and low odor
- Excellent protection against the toughest oil and water-based stains
- This product may help you achieve LEED certification

For more information on this product and other products for tile and stone care, please visit your distributor or our website at www.ecostonesolutions.com.